

**SOAKAWAY PIT INSPECTION & MAINTENANCE**





- Downspout filters to be inspected and cleared of any accumulated leaves, debris, or sediment at a minimum once annually and/or following every major storm event (>25 mm).
- A water level inspection of the soakaway pit is to be performed via the monitoring well at least 72 hours following every major storm event (>25 mm) to ensure the system is operating as designed.
- Ensure the monitoring well plug is fastened securely in order to impede leaves, debris and sediment from entering the system. Keep lid flush to grade to avoid potential tripping hazards in landscaped areas.

**SOAKAWAY PIT/INFILTRATION SYSTEM CONSTRUCTION CONSIDERATIONS**

- Soakaway/infiltration systems to be located a minimum of 5.0 m from any foundation wall.
- Heavy equipment and traffic should avoid traveling over the proposed location of the soakaway pits to minimize the compaction of the soil.
- Soakaway pits should be kept "off-line" until construction is complete. They should never serve as a sediment control device during construction. Sediment should be prevented from entering the facility.
- Upland drainage areas to be stabilized following construction to reduce sediment loads.
- The soakaway pits should be excavated to design dimensions from the side using a backhoe or excavator. The base of the facility should be level or nearly level.

**GROUNDWATER LEVEL NOTE:**

From Toronto Inspections Ltd. Hydrogeological Investigation prepared February 10, 2021 all monitoring wells were installed to a minimum depth of 6.1 m below the ground surface and were found to be dry. All proposed infiltration systems are proposed to have the underside to be within 3.0 m of the existing grade, except Block 6 - Unit 2 soakaway pit which will have its underside at ±4.0 m below the existing grade. The closest monitoring well is 20BH-1(MW) which was drilled to 12.3 m depth and groundwater level was found to be at 11.88 m deep. Therefore all proposed infiltration/soakaway systems are more than 1.0 m above the measured water levels.



KEY PLAN - NOT TO SCALE

**LEGEND**

- DENOTES LIMIT OF PROPERTY
- 296.81 DENOTES PROPOSED GRADE
- 296.81SW DENOTES PROPOSED SWALE GRADE
- 296.81HP DENOTES PROPOSED SWALE HIGH POINT GRADE
- 296.81G DENOTES PROPOSED GUTTER GRADE
- [299.81] DENOTES FUTURE GRADE
- 296.79 DENOTES EXISTING ELEVATION
- (296.79) DENOTES INTERPOLATED EXISTING ELEVATION
- S DENOTES SPLIT DRAINING LOT TYPE
- B/S DENOTES BACK-SPLIT LOT TYPE
- W/O DENOTES WALKOUT LOT TYPE
- ⊙ DENOTES PROPOSED STORM MANHOLE
- ⊙ DENOTES PROPOSED SANITARY MANHOLE
- ⊙ DENOTES PROPOSED CATCHBASIN
- ⊙ DENOTES PROPOSED PUP CATCHBASIN
- ⊙ DENOTES PROPOSED DOUBLE CATCHBASIN
- ⊙ DENOTES PROPOSED VALVE & BOX
- ⊙ DENOTES PROPOSED HYDRANT & VALVE
- ⊙ DENOTES PROPOSED DRAINAGE DIRECTION
- ⊙ DENOTES PROPOSED DRAINAGE DIRECTION
- ⊙ DENOTES EXISTING DRAINAGE DIRECTION
- ⊙ DENOTES OVERLAND FLOW ROUTE
- ⊙ 4.0 m OFFSET FROM FOUNDATION WALLS

NOTE: NO STORM CONNECTIONS ARE PROVIDED SINCE THE STORM SYSTEM IS DESIGNED TO SURCHARGE. DWELLINGS WILL BE PROVIDED WITH SUMP PUMPS.

OCS NOTE: MH2 IS TO BE A HYDROWORKS HYDRODOME MODEL HD4.

NO.	DESCRIPTION	DATE

REVISION	

DATE \_\_\_\_\_

PROJECT TITLE  
**PROPOSED RESIDENTIAL SUBDIVISION  
 150 CEMETERY ROAD  
 UXBRIDGE, ONTARIO**

SHEET TITLE  
**PRELIMINARY LID SYSTEMS  
 NOTES & DETAILS PLAN**

POLITIS ENGINEERING LTD.  
 981 GREENWOOD AVENUE  
 TORONTO ONTARIO M4J 4C7  
 TEL. (416) 429 - 8645  
 FAX. (416) 429 - 8951

DESIGNED BY: T.P. CHECKED BY: T.P.  
 DATE: DECEMBER 2021 PROJECT No.: 21575  
 SCALES: SCALE - AS SHOWN DWG. No. **303**